

Beakers, PMP, transparent, squat form, BS 5404 : Part 1

02

Excellent chemical resistance and heat tolerance; will withstand temperatures up to 180°C.
With spout and graduations. Not suitable for use with hotplates.

Catalogue No	Alt. No	Capacity, mL	Subdivisions, mL	Height, mm	O.D., mm	Pack qty
BNH-740-010W	BDB 312P	25	2.5	40	42	10
BNH-740-030Q	BDB 318P	50	5	51	51	10
BNH-740-050K	BDB 324P	100	10	62	62	10
BNH-740-070E	BDB 330P	250	25	82	82	5
BNH-740-080B	BDB 334P	400	50	95	94	5
BNH-740-090V	BDB 336P	500	50	101	100	5
BNH-740-100V	BDB 338P	600	50	107	106	5
BNH-740-110S	BDB 340P	1,000	100	126	127	1
BNH-740-130M	BDB 342P	2,000	50	160	158	1



Beakers, polypropylene, tapered, moulded graduations

02

- Tapered stacking beaker designed and manufactured to ISO 7056
- Moulded graduations and precise non-drip spout, allowing easy pouring
- Autoclavable up to 121°C

Catalogue No	Alt. No	Capacity, mL	Subdivisions, mL	Height, mm	O.D., mm	Pack qty
BNH-650-010A	BPM0025P	25	5	51	41.5	10
BNH-650-015Y	BPM0050P	50	10	61	50.5	10
BNH-650-020P	BPM0100P	100	20	73	61.5	10
BNH-650-025F	BPM0250P	250	50	96	80.5	10
BNH-650-030R	BPM0500P	500	50	121	102.5	10
BNH-650-035H	BPM1000P	1,000	100	148	120	5
BNH-650-040J	BPM2000P	2,000	200	188	163	1
BNH-650-045E	BPM3000P	3,000	200	214	172	1
BNH-650-050L	BPM5000P	5,000	500	250	230	1



Beakers, polypropylene, translucent, squat form, BS 5404 : Part 1

02

Excellent chemical resistance, will withstand temperatures up to 135°C.
With spout and graduations. Not suitable for use with hotplates. Autoclavable.

Catalogue No	Alt. No	Capacity, mL	Subdivisions, mL	O.D., mm	Height, mm	Pack qty
BNH-700-010E	BDA 208P	10	1	32	32	10
BNH-700-020B	BDA 212P	25	2.5	42	40	10
BNH-700-030V	BDA 218P	50	5	51	51	10
BNH-700-050P	BDA 224P	100	10	62	62	10
BNH-700-070J	BDA 230P	250	25	82	82	10
BNH-700-090D	BDA 234P	400	50	94	95	10
BNH-700-101B	BDA 236P	500	50	100	101	10
BNH-700-110A	BDA 238P	600	50	106	107	5
BNH-700-130R	BDA 240P	1,000	100	127	126	5
BNH-700-150L	BDA 242P	2,000	200	158	160	1

